

Submittal Data: 12RLFW ASU12RLF & AOU12RLFW



Job Name: _____ Location: _____

Purchaser: _____

Engineer: _____

Submitted To: _____ For: Reference Approval Construction

Submitted By: _____

Unit Designation: _____ Schedule No. _____ Model No.: _____

Capacities:

Cooling	12,000 BTU/h
Outdoor Design Temp. <i>F° DB/WB</i>	95/75
Heating	16,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
HSPF	11.0
SEER	22.0
EER <i>Cooling/Heating</i>	12.5/12.5
Voltage/Frequency/Phase	208-230/60/1

Indoor Unit:

Noise Level Cooling <i>db (A) - H/ M/ L/ Q</i>	40/ 36/ 30/ 25
Noise Level Heating <i>db (A) - H/ M/ L/ Q</i>	40/ 36/ 31/ 25
Weight	18 lbs.

Outdoor Unit:

Noise Level <i>Cooling/Heating</i>	49/49
Recommended Fuse Size	15A
Min. Ampacity	5.9A
Running Current <i>Cooling</i>	6.5A
Running Current <i>Heating</i>	9.0A
Weight	71 lbs.

Refrigerant Piping:

Max Ht. Difference	49 ft.
Max Total or Combined Length	66 ft.
Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	3/8 in.

- ◆ Seven year compressor warranty
- ◆ Five year parts warranty
- ◆ Digital wireless remote control
- ◆ Auto Louver: Up/Down
- ◆ ENERGY STAR® Qualified
- ◆ Built in Low Ambient to 14°F
- ◆ Auto Restart/ Reset
- ◆ 24 hour timer
- ◆ Optional Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Quiet Mode

Notes:

OUTLINE AND DIMENSIONS

